

**Additivo PR**

Filmig accelerator for coatings and paints, ideal for harsh climates.

**MAIN AREAS OF USE****It is particularly suitable to:**

Accelerate the binding start at low temperatures of paste coatings.

**Recommended applications:**

Improve the drying of coatings and paints at any temperature, as long as the ambient humidity is <95%.

Suitable coatings, micro-coatings and paints:

- Acrylic base
- Siloxane base
- Acryl-siloxane base

**CHARACTERISTICS**

**Simple to dose** it is sufficient to add one bottle per coat bucket.

**Optimises delivery times** allowing you to work without delays in harsh climates.

**METHODS OF APPLICATION****Preparation of the product**

- 1\_Add Additivo PR to the coating to be treated following the doses reported.
- 2\_Mix the decorative product for 5-6 minutes with a low speed mixing drill.
- 3\_Let the product at rest for at least 6 – 8 minutes, and in any case until the incorporated air has been released.
- 4\_Proceed with the application following the relevant technical instructions.

**PRODUCT INFORMATION**

Appearance/Colour	Liquid - Colourless
Particle size	<0.5 mm
Yield/Consumption	Paints: 1 bottle per approx. 20 kg Coatings: 1 bottle per approx. 25 kg
Dilution	Ready to use
Specific gravity	1.05 kg/L
Storage in unopened original packaging	12 months in a dry place between +5° and +35°C
Packaging	Bottle 250 ml
Limit value EU VOC Dir. 2004/42/EC	<30 g/L

**WARNINGS**

- Product for professional use.
- In the case of applications other than those indicated in the sheet, it is advisable to carry out a suitability check in advance and/or contact the Licata Technical Service for further information.
- Always check the colour, texture and appearance before application. Any claims regarding this will not be accepted once the product has been applied.
  - Do not apply in extreme conditions such as on icy surfaces or in the presence of fog/excessive ambient humidity.
- To avoid aesthetic and functional defects, adequate shielding must be provided in case of direct exposure to sunlight.
- Make sure that the ambient, substrate and product temperatures during application and drying are between +5°C and +35°C.
  - Properly care for the product until it is completely dry and at least in the first 48-72 hours, protecting it from rain, wind, weather and direct sunlight.
  - The temperature and humidity can accelerate (if high) or slow down (if too low) even drastically the maturation process, until it stops completely.
  - The presence of scaffolding, the use of natural raw materials and the impossibility of controlling the atmospheric and substrate conditions can lead to signs of recovery and inhomogeneity for which Licata SpA is not responsible.
  - The fresh product can be washed with water.

**SAFETY**

Protect eyes and hands during application.  
Read and keep the latest version of the Safety Data Sheet available for information on the correct disposal, storage and handling of the product.

**NOTES**

This data sheet replaces and voids all previous versions.  
The instructions and performance information given in this document are based on our current technical-scientific knowledge and must in any case be considered purely indicative and refer to standard laboratory conditions. The purchaser must, therefore, check that the product is suitable for his specific requirements. All the documentation necessary for the safe use of Licata SpA products is available in its most up-to-date form on the **Licata SpA** company website. Additionally, our technical-commercial network guarantees a quick inquiry and remains available to you for information and explanations. For further information, contact the Licata Technical Service at [servizio-tecnico@licataspa.it](mailto:servizio-tecnico@licataspa.it)  
**Data sheet ref.: TDS P10860 - rev.10/21.**