

Elasto Primer

Ready-to-use, elastic, consolidating and transparent water-based primer.

**MAIN AREAS OF USE****It is particularly suitable to:**

the preparation for the laying of decorative elastomeric coatings, even on smooth or absorbent surfaces such as wood and plasterboard.

Recommended applications:

It is particularly compatible with acrylic-based or non-transpiring materials.

Suitable substrates (indoors or outdoors):

- Lime, cement or lime/cement-based plasters
- Reinforced skim coats
- Precast and cast-in-place concrete
- Old paint or coatings
- Absorbent substrates
- Flaking substrates
- Gypsum and plasterboard
- External thermal insulation composite systems

CHARACTERISTICS

High binding power ensured by the latest generation of acrylic polymers.

The very high elasticity makes it particularly suitable as a primer for elastomeric cycles.

The ability to expand allows you to effectively mask porous façades.

Excellent penetration limits the excessive absorption of porous surfaces.

Universally compatible with the most common substrates used in construction.

METHODS OF APPLICATION**Preparation of the substrate**

The substrate must be clean, flat, cohesive and free of any kind of release agent.

- **New substrates, well cohesive:** no precautions beyond those indicated.
- **Deteriorated or crumbling substrates:** Remove any friable or poorly cohesive parts and restore the correct flatness. The **licatarepair** and **licatacem** lines are particularly suitable.

Preparation of the product

1_ **Elasto Primer** is ready to use and dilution is not recommended.

2_ Homogenise the product with a mixer at low speed.

Application

1_ Spread **Elasto Primer** in one coat, with a brush or roller, taking care to cover 100% of the surface to be treated.

2_ In the case of crumbling surfaces, apply the product in one or more coats until the desired consolidation is obtained.

PRODUCT INFORMATION

Appearance	Liquid - Colourless
Yield	0.200 – 0.250 m ² /L
Dilution	Ready to use
Drying time	Dry to the touch about 1-2 hours Completely dry about 24 hours
Storage in unopened original packaging	12 months in a dry place between +5° and +35°C
Packaging	10 L polypropylene bucket
Binding agent	Elastomeric copolymer
VOC (Directive 2004/42/EC) for coating for external walls (Cat A/c):	< 30g/L of VOC

WARNINGS

- Product for professional use.

In the case of applications other than those indicated in the sheet, it is advisable to carry out a suitability check in advance and/or contact the Licata Technical Service for further information.

- Always check the colour, texture and appearance before application. Any claims regarding this will not be accepted once the product has been applied.
- Do not apply in extreme conditions such as on icy surfaces or in the presence of fog/excessive ambient humidity.

To avoid aesthetic and functional defects, adequate shielding must be provided in case of direct exposure to sunlight.

- Make sure that the ambient, substrate and product temperatures during application and drying are between +5°C and +35°C.
- Properly care for the product until it is completely dry and at least in the first 48-72 hours, protecting it from rain, wind, weather and direct sunlight.
- The temperature and humidity can accelerate (if high) or slow down (if too low) even drastically the maturation process, until it stops completely.
- The presence of scaffolding, the use of natural raw materials and the impossibility of controlling the atmospheric and substrate conditions can lead to signs of recovery and inhomogeneity for which Licata SpA is not responsible.
- The fresh product can be washed with water.

SAFETY

Protect eyes and hands during application.

Read and keep the latest version of the Safety Data Sheet available for information on the correct disposal, storage and handling of the product.

NOTES

This data sheet replaces and voids all previous versions.

The instructions and performance information given in this document are based on our current technical-scientific knowledge and must in any case be considered purely indicative and refer to standard laboratory conditions. The purchaser must, therefore, check that the product is suitable for his specific requirements. All the documentation necessary for the safe use of Licata SpA products is available in its most up-to-date form on the **Licata SpA** company website. Additionally, our technical-commercial network guarantees a quick inquiry and remains available to you for information and explanations. For further information, contact the Licata Technical Service at servizio-tecnico@licataspa.it

Data sheet ref.: TDS P10550 - rev.10/21.